

315 CYPRESS LN, EL CAJON CA 92020

Weight

2,250 lbs

2,850 lbs

3,380 lbs

4,130 lbs

4,970 lbs

5,665 lbs

6,720 lbs

10,750 lbs

4,120 lbs

4,790 lbs

5,970 lbs

7,220 lbs

7,896 lbs

11,394 lbs

2,990 lbs

Size

4' x 8'

4' x10'

Socal H

4' x 8' x 4"

4' x 10' x 4"

4' x 12' x 4"

4' x 16' x 4"

4' x 20' x 4"

4' x 24' x 4"

4' x 28' x 4"

4' x 32' x 4"

6' x 10' x 4"

6' x 12' x 4"

6' x 16' x 4"

6' x 20' x 4"

6' x 24' x 4"

6' x 24 x 6"

8' x 8' x 4"

Size

SHORING AND PLATES

Shield

Size

8' x 10' x 4"

8' x 12' x 4"

8' x 16' x 4"

8' x 20' x 4"

8' x 24' x 4"

8' x 24' x 6"

8' x 28' x 6"

8' x 32' x 8"

10' x 10' x 4"

10' x 12' x 4"

10' x 16' x 4"

10' x 20' x 4"

10' x 24' x 6"

10' x 28' x 6"

10' x 32' x 8"

Weight

1,262 lbs

1,481 lbs

Trench Boxes

Size

6' x12'

6' x16'

Trench Boxes

Pipe Spreader - 41 lbs per ft

Weight

5.090 lbs

6,000 lbs

7.154 lbs

8,920 lbs

11,420 lbs

12,290 lbs

12,320 lbs

20,224 lbs

6,268 lbs

7,432 lbs

9,040 lbs

619.334.3900


Steel Crossing Plates


SoCal SHIELD.com

8" x 10" Track Out Plates 36" Manhole Covers

Size	Weight	Size	Weight
5126		5126	weight
4' x 6'	984 lbs	8' x 12'	3,936 lbs
4' x 8'	1,312 lbs	8' x 12' x 1 ¹ / ₂ "	5,953 lbs
4' x 10'	1,640 lbs	8' x 15'	4,920 lbs
5' x 8'	1,640 lbs	8' x 15' x 1 ¹ /2"	7,440 lbs
5' x 10'	2,050 lbs	8' x 16'	5,228 lbs
6' x 8'	2,734 lbs	8' x 16' x 1 ¹ /2"	7,936 lbs
6' x 10'	2,450 lbs	8' x 20' x 1"	6,539 lbs
6' x 12'	2,952 lbs	8' x 20' x 1 ¹ / ₂ "	9,920lbs
8' x 10'	3,280 lbs		

回時時 208







TEN COMMANDMENTS OF TRENCHING

- A competent person must inspect, classify soils and document trench conditions prior to the start of work and prior to employee entrance
- 2. Proper sloping or trench protection must exist at 5 feet or deeper
- 3 Spoils must be at least 2 feet from edge of trench.
- 4. Ladders or ramps are required when trenches are 4 feet or more in depth.
- 5. 25 feet is the maximum distance a person can be from a ladder or ramp.
- 6. Ladders must be secured in place, extend 3 feet and lead to safe landing.
- 7. All trench shore and shields installed per manufacturer's tabulated data.
- 8. A trench shield must 18 inches above sloped sides and be within 2 feet of bottom of the trench.
- 9. Class B soils must be sloped 1:1. Class C soils must be sloped 1.5:1.
- 10. Have an emergency plan for trench and confined space rescue.